



RE-EMULSIFIER FLOOR FINISH STRIPPER

ONE UP

FLOOR FINISH STRIPPER

This finish stripper solubilizes many coats of finish & seal in one operation. Can be used with or without machine.

Re-Emulsifier Floor Finish Stripper will solubilize polishes to their original liquid state. Stripping is accomplished without the mess and cost of repeat applications. Through advanced technology this product allows you to let the chemical do the work Except for extremely heavy build-up absolutely little machine agitation is necessary. Simply mop on and wet vac or mop off.

Directions:

For complete application instructions see the one up Floor Care Application Training Guide.

LIGHT BUILD UP: Dilute 1 part Re-Emulsifier to 3 parts hot or warm water.

MEDIUM: Dilute 1 part Re-emulsifier to 2 parts hot or warm water.

HEAVY: Dilute 1 part Re-Emulsifier to 1 part hot or warm water. Apply solution to floor so Re-Emulsifier covers approximately 100 square feet. Apply enough material to ensure complete wetting. Allow to stand 3-5 minutes maximum. **DO NOT ALLOW SOLUTION TO DRY.** For best results wet vac residue or if not possible use a damp mop for recovery. Rinse with clear water.

Specifications:

Odor.....	Buty
Appearance.....	Yellow
pH.....	13.0 +/- 0.5
Specific Gravity.....	1.01 +/- 0.5
Dilution.....	1-1/1-3/1-5
Flash Point.....	None

Companion Products:

- Rehab Anti-Slip Restoration Compound
- Film-Free Neutral Cleaner
- Multi-Speed Floor Finish
- Seal Shield Protective Floor Sealer
- ReStorer Mop Down Gloss Refinisher



Manufactured by:
The Bullen Companies, 1640 Delmar Drive, Folcroft, PA 19032
Phone 800-444-8900 • Fax 610-534-8912 • e-mail www.bullenonline.com

MATERIAL SAFETY DATA SHEET

(Prepared According to 29 CFR 1910.1200)

KEY CODE 043

SECTION 1 - PRODUCT IDENTIFICATION

Trade Name ONE UP RE-EMULSIFIER Product Type Floor Finish Stripper

SECTION 2 - HAZARDOUS INGREDIENTS

CHEMICAL NAME/COMMON NAME	CAS NO.	PERCENT(optional)	TLV(Source)
2-butoxyethanol *	111-76-2	10-20	50 ppm(skin)TWA (OSHA):20 ppm(skin)(ACGIH)
2-Aminoethanol	141-43-5		3 ppm TWA (ACGIH): 3 ppm TWA (OSHA)
Potassium Hydroxide	1310-58-3		2 mg/m3(ceiling)(OSHA): 2 mg/m3(ceiling)(ACGIH)
Isopropyl Alcohol	67-63-0		OSHA Permissible Exposure Limit (PEL): 400 ppm
Aliphatic Phosphate Ester	Proprietary		Not established

SARA HAZARD TITLE III. SECTION 313-CONTAINS THE STARRED INGREDIENT(S) AT THE INDICATED PERCENTAGES
 Other ingredients in this product are : Less than 1% by weight or less than 0.1% for carcinogens Not hazardous Declared to be Trade Secret

SECTION 3 - PHYSICAL DATA

Boiling point(°F.) near 212 Specific Gravity(H₂O=1.0) (± 0.005) 1.015 pH (± 0.5) 13.5
 Vapor Pressure(mm Hg) Unknown Vapor Density(Air=1) Unknown
 Solubility in water Complete Insoluble Emulsifiable (or Dispersible) Slight (or Partial)
 Evaporation Rate(vs. H₂O) Faster Slower About the Same
 Appearance and Odor Liquid, "butyl" odor

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flash Point(T.C.C.) >141 °F. None to Boiling Flammable Limits Upper Unknown Lower Unknown
 Extinguishing Media CO₂, dry chemical, foam, water spray.
 Special Firefighting Procedures Do not enter confined fire-spaces without protective clothing and self-contained air supply.
 Unusual Fire and Explosion Hazards None known.

SECTION 5 - REACTIVITY DATA

Stability Stable Incompatibility Strong oxidizers
 Hazardous Decomposition Products Carbon monoxide and other unidentified organic gases may occur during incomplete combustion.

SECTION 6 - HEALTH HAZARDS

Primary Routes of Exposure Eye Skin Oral Inhalation Other
 Signs and Symptoms of Overexposure (Acute) Prolonged/repeated contact of concentrated product with skin/eyes can cause chemical burns. If taken internally, concentrated product may cause damage to mouth, throat or stomach. Inhalation of mist or spray may cause irritation to nose, throat or lungs if adequate ventilation is not employed. Ingestion, prolonged or widespread contact of product of concentrate may result in potentially harmful absorption. Nausea/dizziness may result from breathing vapors of concentrate in enclosed/confined spaces.
 Signs and Symptoms of Overexposure(Chronic) None known
 Medical Conditions Aggravated by Overexposure None known Carcinogen/Suspect Carcinogen Ingredients NTP OSHA IARC NONE

SECTION 7 - EMERGENCY AND FIRST AID PROCEDURES

Eyes Flush immediately with water for at least 15 minutes. Call a physician.
 Skin Flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing/ shoes. Call a physician. Wash clothing before reuse.
 Ingestion If swallowed do NOT induce vomiting. Give large quantities of water, followed by one oz. of vinegar in an equal amount of water. Call a physician.
 Inhalation Remove exposed person to fresh air. Treat symptomatically. Call a physician.

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection Not needed under normal conditions of use.
 Ventilation Requirements Local Exhaust Mechanical Room Ventilation Is Adequate
 Protective Gloves Rubber Eye Protection Safety Glasses Other Protective Clothing Wear rubber overshoes if walking in solution

SECTION 9 - SPILL OR LEAK PROCEDURES

Steps to be Taken if Released or Spilled Small spills: flush area with water and neutralize spill with dilute acids. Large spills: Remove as much material as possible, then neutralize residue as under small spills.
 Waste Disposal Methods Dispose of in accordance with applicable Federal, State and Local ordinances.

SECTION 10 - STORAGE AND HANDLING INFORMATION

Precautions to be Taken in Handling and Storage Do not get in eyes, on skin, on clothing. Avoid breathing vapor or mist. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling.

The health hazards given on the Material Safety Data Sheet apply to this product in its concentrated form (as supplied) and may differ significantly at use dilution. The signs and symptoms of over exposure apply only to negligence in handling or misuse of the concentrated product and not to the routine exposure to the product, under normal conditions of use.